





**FORTEC**  
ELEKTRONIK AG

**POS-Line 64.5**

One look - many functions and options

OUR GLOBAL  
COMPETENCE  
CENTERS



# Panel and Housing

## POS-Line 64.5

	Measure	Description
Panel Diagonal	[mm] / [Inch]	1639.1/ 64.53
Type		Open -frame monitor (various bezels, true-flat glass and touch solutions are available under options)
Resolution	[Pixel]	1920 x 1080 FHD
Luminance (center)	[cd/m <sup>2</sup> ]	500
Viewing angle (U/ D/ L/ R)	[°]	89/ 89/ 89/ 89
Backlight		LED
Active area (H/V)	[mm]	1428.4 x 803.52
Number of colors	[M]	16.7
Contrast ratio		4000:1
Response time (on/off)	[ms]	8
Pixel class		ISO 9241-307 (pixel error class II)
Life time back light until reaching half brightness	[h]	50.000
Continuous operating time	[h] / [d]	24/ 7
Mounting	[mm]	VESA MIS-F 800 x 400 (M6)
Storage temperature	[°C] / [°F]	-20 ~ 60 / -4 ~ 140
Operating temperature	[°C] / [°F]	0 ~ 40/ 32 ~ 104
Storage humidity	[%]	10 ~ 90 (non condensing)
Operating humidity	[%]	10 ~ 90 (non condensing)
Panel orientation		Landscape and Portrait
Location of connectors		Landscape: bottom/ Portrait: left (front view)
Location of OSD buttons		Landscape: bottom/ Portrait: left (front view)
Housing		Powdered steel sheet DC01, black RAL 9005
IP grade		IP 65 on the front if option TrueFlat glass or TrueFlat touch
Power supply	[V]	AC 110 - 240
Conformity		CE, FCC Class A, EU-RoHS
Packaging		Single packaging for one way pallet (max. 2 packages p.p.)
Package Contents		Safety instructions, power cable




Monitor with bezel



All figures are typical values. The real values of the panel may vary. The optical characteristics are determined after the panel has been „ON“ for approximately 30 minutes at an ambient temperature of 25° C (77° F). Life time of the backlight is defined as the time to take until the brightness reduces to 50% of its original value.


# Video PME - VGA, HDMI, Display Port

**POS-Line 64.5**




Order number		DS-91-954
Interfaces		1 x VGA, 1 x HDMI, 1 x DisplayPort, 1 x Audio Line-Out, 1 x USB-Remote, 1 x OSD 4 button
Power consumption (typ.)	[Watt]	180
Weight	[kg]	44.0
Dimensions (W x H x D)	[mm]	1480 x 855 x 122
Package contents		SVGA cable

# VideoPoster - Network Multimediaplayer




Order number		DS-91-956
Interfaces		1 x LAN, 2 x USB, 1 x HDMI, 1 x Line out, 1 x MicroSD card slot
Power consumption (typ.)	[Watt]	170
Weight	[kg]	44.0
Dimensions (W x H x D)	[mm]	1480 x 855 x 122
Package contents		USB Stick 8 GB

# IOT - Raspberry® IoT Controller



POS-Line 64.5




Order number		DS-91-985
Order numbers		DS-60-859
Interfaces		1 x LAN, 2 x USB 2.0, 1 x HDMI, 1 x Line out, 1 x MicroSD card slot, 1 x USB-B (only for content updates)
Raspberry® PI		CM3+, 32 GB
Power consumption (typ.)	[Watt]	170
Weight	[kg]	44.0
Dimensions (W x H x D)	[mm]	1480 x 855 x 122

# IQ Celeron - PC Intel® Celeron®




POS-Line 64.5



Order number		DS-92-187
Interfaces		2 x Gigabit LAN, 4 x USB 3.0, 2 x USB 2.0, 1 x HDMI, 1 x RS232/422/485
PC		Intel® Celeron® J3455 (1,5GHz/2,3GHz), RAM: 4 GB DDR3L, Storage: min. 120 GB mSATA
Fan		no
Power consumption (typ.)	[Watt]	190
Weight	[kg]	44.0
Dimensions (W x H x D)	[mm]	1480 x 855 x 122

# IQ Core-i5 - PC Intel® Core™-i5



Order number		DS-92-026
Features		Resolution 4K external via DisplayPort supported
Interfaces		2 x DP, 2x LAN, 4x USB 3.0, 1 x Audio, 1 x MIC in
PC		Intel® Core™-i5-7300 U (2.6 GHz), Intel® HD Graphics GT series, RAM: 8GB DDR 4 Storage: 120 GB M.2Sata
Fan		no
Power consumption (typ.)	[Watt]	210
Weight	[kg]	46.0
Dimensions (W x H x D)	[mm]	1480 x 855 x 122

# Options

## POS-Line 64.5

Order number		DS-91-951
Name		Front bezel
Finish		Steel, powder coated, black RAL 9005
Can be combined with		Safety glass, ALS, remote control
Weight	[kg]	2.00
Dimensions of monitor with option (W x H x D)	[mm]	1484 x 859 x 123

### Bezel



Front bezel is a metal bezel for the open frame chassis and VESA mount.

Order number		DS-91-950	DS-91-952
Name		Safety glass	TrueFlat glass
Finish		Safety glass TSG, 5 mm anti glare	Safety glass TSG, 5 mm anti glare, printed black passepartout (RAL 9005)
IP grade		–	front IP 65**
Can be combined with		Front bezel, ALS, remote control	–
Weight	[kg]	15.00	18.00
Dimensions of monitor with option (W x H x D)	[mm]	1480 x 855 x 132	1540 x 917 x 130

### Glass\*

Safety glass is an accessory for the open frame chassis. It covers and protects the TFT-panel.

\*Glass and touch screens will reduce monitor brightness.

\*\* depending on the customer's installation

# Accessories

Order number		DS-92-033
Name		PC Box extern IQ Core™-i5 DFI KU173
Description		PC module for external mounting
Interfaces		2 x DP, 2x LAN, 4x USB 3.0, 1 x Audio, 1 x MIC in
PC		Intel® Core™-i5- 7300 U(2.6 GHz), Intel® HD Graphics GT series, RAM: 8GB DDR 4 Storage: min. 120 GB M.2Sata
Available for controller		Video PME
Fan		no
Weight	[kg]	2.60
Dimensions of monitor with option (W x H x D)	[mm]	240 x 257 x 48.5
Power supply		DS-91-945 for operate the PC box as stand alone device without display for maintenance, 12V/ 60 W

Order number		DS-92-135
Name		PC-Box IQ Celeron®
Description		PC module for external mounting
Interfaces		2 x Gigabit LAN, 4 x USB 3.0, 2 x USB 2.0, 1 x HDMI, 1 x RS232/422/485
PC		Intel® Celeron® J3455 (1,5GHz/2,3GHz), RAM: 4 GB DDR3L Storage: min. 120 GB mSATA
Available for controller		Video PME
Fan		no
Weight	[kg]	1.70
Dimensions of monitor with option (W x H x D)	[mm]	240 x 260 x 50
Power supply		DS-91-945 for operate the PC box as stand alone device without display for maintenance, 12V/ 60 W

## POS-Line 64.5

### External PC



Optional removable PC box with Core-i5 CPU. The PC box can be removed without taking the display down from the wall.



Optional removable PC box with Intel Celeron CPU. The PC box can be removed without taking the display down from the wall.

# Accessories

## POS-Line 64.5

Product	Order no.	Product description
Remote control	DS-91-964	OSD remote controll for 64.5 displays of the Video PME series
Ambient Light Sensor	DS-91-963	ALS for all displays of the Video PME and VideoPoster, can be combined with front bezel and safety glass
SSD Extension Celeron®	DS-91-997	Extension for SSD MSATA up to 240 GB for IQ Celeron®
RAM Extension Celeron®	DS-91-975	Extension for RAM up to 8 GB for IQ Celeron®
SSD Extension Core™-i	DS-92-027	Extension for SSD M.2 up to 240 GB for IQ Core™-i5
RAM Extension Core™-i	DS-92-028	Extension for RAM up to 16 GB for IQ Core-i5

### Electronic

Product	Order no.	Product description
Cable DP for PC box	KA-40-115	DP cable for connection PC, 0,5m
Display Port cable	KA-40-105	Cable Display Port 1.2 4k male/male 2m
LAN for remote contr.	DS-92-087	for all versions, LAN RJ 45

### Cable

Product	Order no.	Product description
Windows 10 Pro. 64 bit DE	DS-60-811	Operation system for Celeron and Core-i
Windows 10 Pro. 64 bit EN	DS-60-810	Operation system for Celeron and Core-i
WIN 10 IOT Core™-i	DS-60-898	Embedded operation system 2019 LTSC
WIN 10 IOT Celeron®	DS-60-899	Embedded operation system 2019 LTSC
WebPoster IQ	DS-60-787	WEBPOSTER embedded Linux for IQ

### Software



# Accessories

## POS-Line 64.5

### Mounts and Covers

Product	Order no.	Product description
Wall mount	DS-91-101	Inclinable wall mount for all displays from 46" up to 64.5"
Cable cover for connctetors	DS-91-960	Cover for the cable connectors to prevent unauthorized persons from removing or plugging cables. For all POS-Line displays of the PME series 64.5"
Cable cover for connctetors	DS-91-961	Cover for the cable connectors to prevent unauthorized persons from removing or plugging cables. For all POS-Line displays of the IQ Series 64.5". Also suited for optional PC boxes DS-92-033 and DS-92-135.
Cable cover for connctetors	DS-91-962	Cable cover. Only available in combination with covers DS-91-960 and DS-91-961.

Various accessories are available for POS-Line monitors.

All monitors can be customized according to your specific requirements.

Please contact our sales team if you are interested in product modifications or custom designs.

Copyright 2022 Distec GmbH.  
Information in the document is subject to change without prior notice.

Our company network supports you worldwide with offices in Germany, Austria, Switzerland, the UK and the USA. For more information please contact:

Contact

Headquarters

Germany



**FORTEC Elektronik AG**  
Augsburger Str. 2b  
82110 Germering

Phone: +49 89 894450-0  
E-Mail: [info@fortecag.de](mailto:info@fortecag.de)  
Internet: [www.fortecag.de](http://www.fortecag.de)

Fortec Group Members

Austria



**Distec GmbH**  
Office Vienna  
Nuschingasse 12  
1230 Wien

Phone: +43 1 8673492-0  
E-Mail: [info@distec.de](mailto:info@distec.de)  
Internet: [www.distec.de](http://www.distec.de)

Germany



**Distec GmbH**  
Augsburger Str. 2b  
82110 Germering

Phone: +49 89 894363-0  
E-Mail: [info@distec.de](mailto:info@distec.de)  
Internet: [www.distec.de](http://www.distec.de)

Switzerland



**ALTRAC AG**  
Bahnhofstraße 3  
5436 Würenlos

Phone: +41 44 7446111  
E-Mail: [info@altrac.ch](mailto:info@altrac.ch)  
Internet: [www.altrac.ch](http://www.altrac.ch)

United Kingdom



**Display Technology Ltd.**  
Osprey House, 1 Osprey Court  
Hinchingsbrooke Business Park  
Huntingdon, Cambridgeshire, PE29 6FN

Phone: +44 1480 411600  
E-Mail: [info@displaytechnology.co.uk](mailto:info@displaytechnology.co.uk)  
Internet: [www.displaytechnology.co.uk](http://www.displaytechnology.co.uk)

USA



**Apollo Display Technologies, Corp.**  
87 Raynor Avenue,  
Unit 1 Ronkonkoma,  
NY 11779

Phone: +1 631 5804360  
E-Mail: [info@apollodisplays.com](mailto:info@apollodisplays.com)  
Internet: [www.apollodisplays.com](http://www.apollodisplays.com)